

Datum: 02.07.2026



krog. ventil med., pnevm. vklop enojno delovanje, 1 1/4

Kategorija: [Brass ball valve, single-acting actuator](#)
Šifra: **103575RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, single-acting,
Operating temperature -20°C to 150°C, Rp 1 1/4, DN 32, PN
max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker
principle.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1 1/4
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Max. vodeni tlak [bar]	5.6
Max. obratovalni tlak [bar]	16
DN	32
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
L [mm]	103.0
B [mm]	131.0
Max. delovna temperatura [°C]	150
A [mm]	221.0