



(slika je simbolična)

## [krog. ventil med., pnevm. vklop enojno delovanje, 1/2](#)

Kategorija: [Brass ball valve, single-acting actuator](#)  
Šifra: **103572RIE**

### Kratek opis

Brass ball valve, Pneumat. actuation drive, single-acting,  
Operating temperature -20 °C to 150 °C, Rp 1/2, DN 15, PN  
max. 16 bar  
Ball valves with pneumatic actuator.  
Pneumatic, double-piston, part-turn actuator, double-rocker  
principle.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Max. vodeni tlak [bar]	5.6
DN	15
Max. obratovalni tlak [bar]	16
L [mm]	69.0
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
B [mm]	110.0
Max. delovna temperatura [°C]	150
A [mm]	221.0