

krog. ventil med., pnevm. vklop enojno delovanje, Rp 1 1/2



Kategorija: [Brass ball valve, single-acting actuator](#)
Šifra: **158751RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, NAMUR, single-acting, Operating temp. -20°C to 150°C, Rp 1 1/2, DN 40, PN max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

| | |
|--|---|
| Min. delovna temperatura aktuatorja [°C] | -20 |
| Min. delovni tlak krogelnega ventila [°C] | -20 |
| Adapter ventila | Integrated to NAMUR Nickel-plated brass, with flange plate ISO 5211 |
| Material krogelnega ventila | Rp 1 1/2 |
| Navoj | Anodised aluminium |
| Pogonski material | PTFE / FKM |
| Premaz za krogelni ventil | NBR |
| Premaz za pogon | single-acting - spring to close |
| Različica | |
| Priporočeni vodeni tlak [bar] | 5.6 |
| Max. vodeni tlak aktuatorja [bar] | 8.4 |
| Max. delovni tlak krogelnega ventila [bar] | 16 |
| DN | 40 |
| Max. delovna temperatura aktuatorja [°C] | 80 |
| Kot vrtenja [°] | 90 |
| L [mm] | 114.0 |
| B [mm] | 136.8 |
| Max. delovni tlak krogelnega ventila [°C] | 150 |
| A [mm] | 233.2 |