

krog. ventil med., pnevm. vklop enojno delovanje, Rp 1 1/4

Kategorija: [Brass ball valve, single-acting actuator](#)
Šifra: **158750RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, NAMUR, single-acting, Operating temp. -20°C to 150°C, Rp 1 1/4, DN 32, PN max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Integrated to NAMUR Nickel-plated brass, with flange plate ISO 5211
Material krogelnega ventila	Rp 1 1/4
Navoj	Anodised aluminium
Pogonski material	PTFE / FKM
Premaz za krogelni ventil	NBR
Premaz za pogon	single-acting - spring to close
Različica	
Priporočeni vodeni tlak [bar]	5.6
Max. vodeni tlak aktuatorja [bar]	8.4
Max. delovni tlak krogelnega ventila [bar]	16
DN	32
Max. delovna temperatura aktuatorja [°C]	80
Kot vrtenja [°]	90
L [mm]	103.0
B [mm]	129.8
Max. delovni tlak krogelnega ventila [°C]	150
A [mm]	233.2