

Datum: 01.07.2026



(slika je simbolična)

krog. ventil med., pnevm. vklop vzmetno odpiranje, 2

Kategorija: [Brass ball valve, single-acting actuator](#)Šifra: **103546RIE**

Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring opening, Operating temp. max. 70 °C, Rp 2, DN 50, PN max. 25 bar
2-way cock, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

| | |
|-----------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Adapter ventila | Supplied as standard |
| Material krogelnega ventila | Nickel-plated brass, with ISO flange plate |
| Navoj | Rp 2 |
| Pogonski material | Anodised aluminium |
| Premaz za krogelni ventil | PTFE / FKM |
| Premaz za pogon | NBR |
| Različica | single-acting - spring to open |
| Priporočeni vodeni tlak [bar] | 5.5 |
| Max. vodeni tlak aktuatorja [bar] | 10 |
| PN [bar] | 25 |
| D [mm] | 45.0 |
| DN | 50 |
| a/f [mm] | 70 |
| Max. delovna temperatura [°C] | 70 |
| Kot vrtenja [°] | 90 |
| L [mm] | 140.0 |
| A [mm] | 180.0 |
| B [mm] | 203.0 |