

Datum: 01.07.2026



[krog. ventil med., pnevm. vklop vzmetno odpiranje, 1/2](#)

Kategorija: [Brass ball valve, single-acting actuator](#)Šifra: **103540RIE**

(slika je simbolična)

Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring opening, Operating temp. max. 70 °C, Rp 1/2, DN 15, PN max. 40 bar
2-way cock, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to open
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
DN	15
D [mm]	17.0
a/f [mm]	26
PN [bar]	40
Max. delovna temperatura [°C]	70
L [mm]	75.0
Kot vrtenja [°]	90
A [mm]	133.0
B [mm]	142.0