

Datum: 13.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[krog. ventil ner.jeklo, 2-delno, IT/ET z navojem, G 2, DN 50](#)

Kategorija: [Stainless stell ball valve, 2-piece, IT/ET thread](#)
Šifra: **135909RIE**

Kratek opis

Stainless steel ball valve, 2-piece, IT/ET thread, G 2, DN 50,
Operating temperature -20 °C to 180 °C, PN max. 63 bar

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock	ca. 6.0 mm
Krogelno tesnilo	PTFE (15 % glass fibre reinforced)
Krogla	Stainless steel 1.4401
Navoj	G 2
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE
C Ø [mm]	49.0
DN	50
PN [bar]	63
B [mm]	111.0
L [mm]	123.0
A [mm]	170.0
Max. delovna temperatura [°C]	180