

Datum: 04.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[krog. ventil ner.jeklo, 2-delno, IT/IT z navojem, G21/2,DN65](#)

Kategorija: [Stainless stell ball valve, 2-piece, IT/IT thread](#)
Šifra: **135900RIE**

Kratek opis

Stainless steel ball valve, 2-piece, IT/IT thread, G 2 1/2, DN 65, Operating temperature -20 °C to 180 °C, PN max. 40 bar

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock	ca. 6.0 mm
Krogelno tesnilo	PTFE (15 % glass fibre reinforced)
Krogla	Stainless steel 1.4401
Navoj	G 2 1/2
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE
PN [bar]	40
DN	65
B [mm]	135.0
L [mm]	138.0
Max. delovna temperatura [°C]	180
A [mm]	240.0