

[krog. ventil, osnovna obilka, IT/IT, nikljana med., G 1 1/2](#)



Kategorija: [Ball valve with hand lever red, standard type, IT/IT](#)

Šifra: **103099RIE**

(slika je simbolična)

Kratek opis

Ball valve, Manual lever, Standard type, IT/IT, nickel-plated brass, Operating temp. -20°C to 150°C, G 1 1/2, DN 40, PN max. 30bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems and air conditioning systems.

Tehnične Specifikacije

| | |
|---------------------|--|
| Delovna temperatura | -20 °C to 150 °C (no steam) |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material | Nickel-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | G 1 1/2 |
| Ročica | Galvanised steel, painted red |
| Standardni navoj | G-thread acc. to DIN EN ISO 228-1, tolerance class B |
| Stebelno tesnilo | NBR / FKM (Seal package consists of 2 O-rings) |
| E [mm] | 17.5 |
| F [mm] | 18.5 |
| PN [bar] | 30 |
| DN | 40 |
| B [mm] | 81.0 |
| L [mm] | 94.5 |
| A [mm] | 138.0 |