

Datum: 09.05.2026



(slika je simbolična)

[krog. ventil robustnejša oblika, metuljasta ročica, IT/ET, G/R 1](#)

Kategorija: [Ball valve with butterfly handle, IT/ET](#)
Šifra: **103296RIE**

Kratek opis

Ball valve heavy duty design, Butterfly handle, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 1, PN max. 80 bar
Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass Brass with a bare metal surface
Material navojev	G/R 1
Navoj	Nickel-plated brass
Ohišje	Aluminium, painted black
Ročica - metuljček	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Standardni navoj	PTFE
Stebelno tesnilo	14.5
F [mm]	19.0
E [mm]	25
DN	39
a/f 2 [mm]	40
a/f 1 [mm]	70.0
A [mm]	70.5
B [mm]	80
PN [bar]	88.4
L [mm]	130
Max. delovna temperatura [°C]	