



(slika je simbolična)

Krog. ventil robustnejša oblika,metuljasta ročica, IT/ET, G/R 3/4

Kategorija: [Ball valve with butterfly handle, IT/ET](#)
Šifra: **103295RIE**

Kratek opis

Ball valve heavy duty design, Butterfly handle, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 3/4, PN max 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G/R 3/4
Ohišje	Nickel-plated brass
Ročica - metuljček	Aluminium, painted black
Standardni navoj	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
F [mm]	13.0
E [mm]	16.0
DN	20
a/f 2 [mm]	32
a/f 1 [mm]	33
A [mm]	55.0
B [mm]	58.5
L [mm]	77.0
PN [bar]	80
Max. delovna temperatura [°C]	130