

Datum: 03.07.2026



(slika je simbolična)

Krog. ventil robustnejša oblika, z ročico, ročni, IT/ET, G/R 1 1/4

Kategorija: [Ball valve with hand lever, IT/ET](#)
Šifra: **103276RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 1 1/4, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G/R 1 1/4
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
F [mm]	16.0
E [mm]	21.2
DN	32
a/f 1 [mm]	49
a/f 2 [mm]	50
PN [bar]	80
B [mm]	95.0
L [mm]	100.0
Max. delovna temperatura [°C]	130
A [mm]	150.0