



(slika je simbolična)

krog. ventil robustnejša oblika, Z ročico, ročni, IT/ET, G/R 1/4

Kategorija: [Ball valve with hand lever, IT/ET](#)
Šifra: **103271RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, IT/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, G/R 1/4, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

| | |
|-------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Brass with a bare metal surface |
| Navoj | G/R 1/4 |
| Ohišje | Nickel-plated brass |
| Ročica | Aluminium, painted black |
| Standardni navoj | G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1) |
| Stebelno tesnilo | PTFE |
| F [mm] | 7.0 |
| DN | 8 |
| E [mm] | 11.0 |
| a/f 1 [mm] | 18 |
| a/f 2 [mm] | 18 |
| L [mm] | 49.0 |
| B [mm] | 51.5 |
| A [mm] | 75.0 |
| PN [bar] | 80 |
| Max. delovna temperatura [°C] | 130 |