

Datum: 01.07.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[krog. ventil robustnejša oblika, Z ročico, ročni, IT/IT, G 2 1/2](#)

Kategorija: [Ball valve with hand lever, IT/IT](#)
Šifra: **103269RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, IT/IT, nickel-plated brass, Operating temp. -20 °C to 130 °C, G 2 1/2, PN max. 40 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G 2 1/2
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE
E [mm]	24.2
F [mm]	24.2
PN [bar]	40
DN	65
a/f [mm]	85
Max. delovna temperatura [°C]	130
L [mm]	148.0
B [mm]	152.0
A [mm]	280.0