



(slika je simbolična)

[krog. ventil standar.obilka, črna jekl. ročica, IT/IT, G 3/4](#)

Kategorija: [Ball valve with black steel lever, IT/IT](#)
Šifra: **103160RIE**

Kratek opis

Ball valve standard design, black steel lever, IT/IT, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 3/4, PN max. 40 bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -15 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material | Nickel-plated brass |
| Material navojev | Brass with a bare metal surface |
| Navoj | G 3/4 |
| Ročica | Steel, with plastic coating |
| Standardni navoj | G thread acc. to DIN EN ISO 228-1 |
| Stebelno tesnilo | 2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE |
| E [mm] | 10.5 |
| F [mm] | 10.5 |
| DN | 20 |
| PN [bar] | 40 |
| B [mm] | 48.4 |
| L [mm] | 58.0 |
| Max. delovna temperatura [°C] | 90 |
| A [mm] | 105.0 |