

Datum: 25.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[krog. ventil standar.oblika, redeča jekl. ročica, IT/ET, G 2](#)

Kategorija: [Ball valve with red steel lever, IT/ET](#)
Šifra: **103210RIE**

Kratek opis

Ball valve standard design, red steel lever, IT/ET, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 2, PN max. 40 bar

Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material	Nickel-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G 2
Ročica	Steel, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
E [mm]	16.5
F [mm]	16.5
PN [bar]	40
DN	50
B [mm]	83.4
Max. delovna temperatura [°C]	90
L [mm]	121.0
A [mm]	165.0