

Datum: 08.04.2026



Krog. ventil za vodo, z ročico, ročni, IT/IT, G 1/2, DN 15

Kategorija: [Potable water ball valves](#)
Šifra: **133163RIE**

(slika je simbolična)

Kratek opis

Potable water ball valve, Nickel-plated brass, Manual lever, IT/IT, G 1/2, DN 15, Operating temp. -15 °C to 110 °C, PN max. 40 bar
Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -15 |
| Aplikacije | Potable water, water DIN EN 13828:2003-12, DVGW W 570 |
| DVGW odobritev | PTFE |
| Krogelno tesnilo | Chrome-plated brass |
| Krogla | Brass |
| Material navojev | G 1/2 |
| Navoj | Nickel-plated brass (outside), brass (inside) |
| Ohišje | Aluminium |
| Ročica | Thread acc. to DIN EN ISO 228-1 |
| Standardni navoj | PTFE / EPDM / HNBR |
| Stebelno tesnilo | 15 |
| DN | 40 |
| PN [bar] | 45.8 |
| B [mm] | 50.0 |
| L [mm] | 85.0 |
| A [mm] | 110 |
| Max. delovna temperatura [°C] | |