

Datum: 01.07.2026



(slika je simbolična)

Krog. ventil za vodo, z ročico, ročni, IT/IT, G 1/2, DN 15

Kategorija: [Potable water ball valves](#)
Šifra: **133163RIE**

Kratek opis

Potable water ball valve, Nickel-plated brass, Manual lever, IT/IT, G 1/2, DN 15, Operating temp. -15 °C to 110 °C, PN max. 40 bar
Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Aplikacije	Potable water, water DIN EN 13828:2003-12, DVGW W 570
DVGW odobritev	PTFE
Krogelno tesnilo	Chrome-plated brass
Krogla	Brass
Material navojev	G 1/2
Navoj	Nickel-plated brass (outside), brass (inside)
Ohišje	Aluminium
Ročica	Thread acc. to DIN EN ISO 228-1
Standardni navoj	PTFE / EPDM / HNBR
Stebelno tesnilo	15
DN	40
PN [bar]	45.8
B [mm]	50.0
L [mm]	85.0
A [mm]	110
Max. delovna temperatura [°C]	