



Krogelni ventil 3/2 »FUTURA-mali«, zaklepni, Velikost 0, G 1/4

Kategorija: [Ball valve](#)
Šifra: **142519RIE**

(slika je simbolična)

Kratek opis

Ball valve 3/2-way »FUTURA-mini«, lockable, Size 0, G 1/4,
Exhaust G 1/4, Input pressure max. 12 bar, Temperature -10
°C to 50 °C

Lockable ball valve, 3/2-way type including silencer,
mechanically operated.

Rotary switch can be turned 90°, with indication of
positions:

Horizontal: Input closed - outlet exhausted

Vertical: Flow open - exhaust closed

Exhaust air can be collected.

Tehnične Specifikacije

| | |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10 |
| Izpušni zrak | G 1/4 At P ₂ = 6 bar and pressure drop Δ _p = 1 bar |
| Merjenje pretoka | G 1/4 PA66 GF60 Plastic FUTURA-mini Compressed air, neutral gases |
| Navoj | G 1/4 |
| Ohišje | PA66 GF60 |
| Priključni navoj | Plastic |
| Serijska | FUTURA-mini |
| Srednje | Compressed air, neutral gases |
| Max. vhodni tlak [bar] | 12 |
| A [mm] | 43.0 |
| Max. temperaturno območje [°C] | 50 |
| C [mm] | 51.0 |
| B [mm] | 87.0 |
| Pretok [l/min] | 2300 |