

Datum: 11.07.2026



## Krogelni ventil 3/2 »FUTURA«, zaklepni, Velikost 1, G 3/8

Kategorija: [Ball valves](#)  
Šifra: **100284RIE**

(slika je simbolična)

### Kratek opis

Ball valve 3/2-way »FUTURA«, lockable, Size 1, G 3/8,  
Exhaust G 1/4, Input pressure max. 16 bar, Temperature -10  
°C to 50 °C

Lockable ball valve, 3/2-way type including silencer,  
mechanically operated.

Rotary switch can be turned 90°, with indication of  
positions:

Horizontal: Input closed - outlet exhausted

Vertical: Flow open - exhaust closed

Exhaust air can be collected.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Izpušni zrak                   | G 1/4<br>At P <sub>2</sub> = 6 bar and<br>pressure drop Δ <sub>p</sub> = 1<br>bar |
| Merjenje pretoka               | G 3/8<br>PA66 GF60  |
| Navoj                          | Material: Die-cast zinc   |
| Ohišje                         | FUTURA  |
| Priključni navoj               | Compressed air,<br>neutral gases  |
| Serijska                       | 1   |
| Srednje                        | 16  |
| Velikost                       | 50  |
| Max. vhodni tlak [bar]         | 52.0  |
| Max. temperaturno območje [°C] | 54.5  |
| A [mm]                         | 87.5  |
| C [mm]                         | 1900  |
| B [mm]                         |   |
| Pretok [l/min]                 |   |