

**Datum:** 23.05.2026



(slika je simbolična)

## [krogelni ventil EN 331, DVGW, metuljasta ročica, IT/IT, Rp 1/4](#)

Kategorija: [Ball valve with butterfly handle, DIN DVGW, IT/IT](#)  
Šifra: **133187RIE**

### Kratek opis

Ball valve EN 331, DVGW, nickel-plated brass, Butterfly handle, IT/IT, Rp 1/4, DN 8, Operat. temp. -15 °C to 60 °C, PN max. 5 bar  
Ball valves with full bore, for gas installations. Applications: Natural gas, LPG, town gas

### Tehnične Specifikacije

Delovna temperatura	-15 °C to 60 °C for gas
Delovni tlak	max. 5 bar (pressure class MOP 5 acc. to DIN EN 331)
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass
Navoj	Rp 1/4
Ohišje	Nickel-plated brass
Ročica - metuljček	Aluminium
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / NBR
DN	8
B [mm]	30.0
L [mm]	45.7
A [mm]	47.0