

Datum: 14.06.2026

**Davčna št.:** SI 56119488  
**Telefon:** 01 500 14 42  
**E-mail:** [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
**WWW:** [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## **krogelni ventil EN 331 DVGW, nisljana medenina, Ročica, Rp 1 1/2**

Kategorija: [Ball valve with hand lever, DIN DVGW, IT/IT](#)  
Šifra: **133175RIE**

### Kratek opis

Ball valve EN 331 DVGW, nickel-plated brass, Hand lever, IT/IT, Rp 1 1/2, DN 40, Operat. temp. -15°C to 60°C, PN max. 5 bar (Gas)  
Ball valves with full bore, for gas installations. Applications: Natural gas, LPG, town gas

### Tehnične Specifikacije

Delovna temperatura	-15 °C to 60 °C for gas
Delovni tlak	max. 5 bar (pressure class MOP 5 acc. to DIN EN 331)
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass
Navoj	Rp 1 1/2
Ohišje	Nickel-plated brass
Ročica	Aluminium
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / EPDM / HNBR
DN	40
B [mm]	76.0
L [mm]	107.7
A [mm]	130.0