

Datum: 14.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



krogelni ventil EN 331 DVGW, nikiplana medenina, Ročica, Rp 1

Kategorija: [Ball valve with hand lever, DIN DVGW, IT/IT](#)
Šifra: **133173RIE**

(slika je simbolična)

Kratek opis

Ball valve EN 331 DVGW, nickel-plated brass, Hand lever, IT/IT, Rp 1, DN 25, Operating temp. -15 °C to 60 °C, PN max. 5 bar (Gas)
Ball valves with full bore, for gas installations. Applications: Natural gas, LPG, town gas

Tehnične Specifikacije

Delovna temperatura	-15 °C to 60 °C for gas
Delovni tlak	max. 5 bar (pressure class MOP 5 acc. to DIN EN 331)
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass
Navoj	Rp 1
Ohišje	Nickel-plated brass
Ročica	Aluminium
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / EPDM / HNBR
DN	25
B [mm]	57.0
L [mm]	83.5
A [mm]	105.0