

Datum: 12.04.2026



(slika je simbolična)

## [krogelni ventil EN 331 DVGW, nikiplana medenina, Ročica, Rp 1](#)

Kategorija: [Ball valve with hand lever, DIN DVGW, IT/IT](#)  
Šifra: **133173RIE**

### Kratek opis

Ball valve EN 331 DVGW, nickel-plated brass, Hand lever, IT/IT, Rp 1, DN 25, Operating temp. -15 °C to 60 °C, PN max. 5 bar (Gas)  
Ball valves with full bore, for gas installations. Applications:  
Natural gas, LPG, town gas

### Tehnične Specifikacije

|                     |  |
|---------------------|--|
| Delovna temperatura | -15 °C to 60 °C for gas                              |
| Delovni tlak        | max. 5 bar (pressure class MOP 5 acc. to DIN EN 331) |
| DVGW odobritev      | DIN EN 331:2013-05                                   |
| Krogelno tesnilo    | PTFE   |
| Krogla              | Chrome-plated brass                                  |
| Material navojev    | Brass  |
| Navoj               | Rp 1   |
| Ohišje              | Nickel-plated brass                                  |
| Ročica              | Aluminium  |
| Standardni navoj    | Thread acc. to ISO 7-1                               |
| Stebelno tesnilo    | PTFE / EPDM / HNBR                                   |
| DN                  | 25   |
| B [mm]              | 57.0   |
| L [mm]              | 83.5   |
| A [mm]              | 105.0  |