

Datum: 13.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[krogelni ventil EN 331 DVGW, nikiplana medenina, Ročica, Rp/R 2](#)

Kategorija: [Ball valve with hand lever, DIN DVGW, IT/ET](#)
Šifra: **133186RIE**

Kratek opis

Ball valve EN 331 DVGW, nickel-plated brass, Hand lever, IT/ET, Rp/R 2, DN 50, Operating temp. -15 °C to 60 °C, PN max. 5 bar
Ball valves with full bore, for gas installations. Applications: Natural gas, LPG, town gas

Tehnične Specifikacije

| | |
|---------------------|--|
| Delovna temperatura | -15 °C to 60 °C for gas |
| Delovni tlak | max. 5 bar (pressure class MOP 5 acc. to DIN EN 331) |
| DVGW odobritev | DIN EN 331:2013-05 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Brass |
| Navoj | Rp/R 2 |
| Ohišje | Nickel-plated brass |
| Ročica | Aluminium |
| Standardni navoj | Thread acc. to ISO 7-1 |
| Stebelno tesnilo | PTFE / EPDM / HNBR |
| DN | 50 |
| B [mm] | 92.0 |
| L [mm] | 134.5 |
| A [mm] | 165.0 |