

Datum: 13.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[krogelni ventil EN 331 DVGW, nikljana medenina, Rp/R 1 1/4](#)

Kategorija: [Ball valve with hand lever, DIN DVGW, IT/ET](#)
Šifra: **133184RIE**

Kratek opis

Ball valve EN 331 DVGW, nickel-plated brass, Hand lever, IT/ET, Rp/R 1 1/4, DN 32, Operating temp. -15 °C to 60 °C, PN max. 5 bar
Ball valves with full bore, for gas installations. Applications: Natural gas, LPG, town gas

Tehnične Specifikacije

Delovna temperatura	-15 °C to 60 °C for gas
Delovni tlak	max. 5 bar (pressure class MOP 5 acc. to DIN EN 331)
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass
Navoj	Rp/R 1 1/4
Ohišje	Nickel-plated brass
Ročica	Aluminium
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / EPDM / HNBR
DN	32
B [mm]	70.0
L [mm]	103.0
A [mm]	130.0