



(slika je simbolična)

## [krogelni ventil EN 331, DVGW, Ročica, nikljana medenina, Rp 1/2](#)

Kategorija: [Ball valves acc. to EN 331 with DIN DVGW](#)  
Šifra: **103304RIE**

### Kratek opis

Ball valve EN 331, DVGW, Hand lever, IT/IT, nickel-plated brass, Operating temp. -20°C to 60°C, Rp 1/2, DN 15, PN max. 5 bar (gas)

Ball valves with full bore, for gas installations.

### Tehnične Specifikacije

|                               |   |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -20   |
| Delovni tlak                  | max. 5 bar (MOP 5) for gas installations acc. to DVGW |
| DVGW odobritev                | DIN EN 331:2013-05                                    |
| Krogelno tesnilo              | PTFE  |
| Krogla                        | Chrome-plated brass (CW617N)                          |
| Material navojev              | Brass   |
| Navoj                         | Rp 1/2  |
| Ohišje                        | Nickel-plated brass                                   |
| Ročica                        | Steel, painted yellow                                 |
| Standardni navoj              | Thread acc. to ISO 7-1                                |
| Stebelno tesnilo              | NBR / FKM   |
| DN                            | 15  |
| E [mm]                        | 15.0  |
| a/f [mm]                      | 25  |
| B [mm]                        | 48.8  |
| Max. delovna temperatura [°C] | 60  |
| L [mm]                        | 61.0  |
| A [mm]                        | 88.5  |