

Datum: 26.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[krogelni ventil EN 331, DVGW, Ročica, nikljana medenina, Rp 1](#)

Kategorija: [Ball valves acc. to EN 331 with DIN DVGW](#)
Šifra: **103306RIE**

Kratek opis

Ball valve EN 331, DVGW, Hand lever, IT/IT, nickel-plated brass, Operating temp. -20°C to 60°C, Rp 1, DN 25, PN max. 5 bar (gas)

Ball valves with full bore, for gas installations.

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -20 |
| Delovni tlak | max. 5 bar (MOP 5) for gas installations acc. to DVGW |
| DVGW odobritev | DIN EN 331:2013-05 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass (CW617N) |
| Material navojev | Brass |
| Navoj | Rp 1 |
| Ohišje | Nickel-plated brass |
| Ročica | Steel, painted yellow |
| Standardni navoj | Thread acc. to ISO 7-1 |
| Stebelno tesnilo | NBR / FKM |
| E [mm] | 19.1 |
| DN | 25 |
| a/f [mm] | 38 |
| B [mm] | 56.8 |
| Max. delovna temperatura [°C] | 60 |
| L [mm] | 85.0 |
| A [mm] | 113.0 |