

Datum: 26.04.2026



(slika je simbolična)

## [krogelni ventil EN 331, DVGW, Ročica, nikljana medenina, Rp 2](#)

Kategorija: [Ball valves acc. to EN 331 with DIN DVGW](#)  
Šifra: **103309RIE**

### Kratek opis

Ball valve EN 331, DVGW, Hand lever, IT/IT, nickel-plated brass, Operating temp. -20°C to 60°C, Rp 2, DN 50, PN max. 5 bar (gas)

Ball valves with full bore, for gas installations.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Delovni tlak	max. 5 bar (MOP 5) for gas installations acc. to DVGW
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 2
Ohišje	Nickel-plated brass
Ročica	Steel, painted yellow
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	NBR / FKM
E [mm]	25.7
DN	50
Max. delovna temperatura [°C]	60
a/f [mm]	66
B [mm]	97.3
L [mm]	130.0
A [mm]	157.8