



## [krogelni ventil fina nastavitvev, nikljana lahka medenina, G 1](#)

Kategorija: [Potable water ball valves with fine adjustment](#)  
Šifra: **103402RIE**

(slika je simbolična)

### Kratek opis

Ball valve fine adjustment, Potable water suitable, nickel-plated bright brass, Temp. -15 °C to 100 °C, G 1, PN max 40 bar

Brass ball valves in the standard series with fine adjustment.

Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line.

The flow rate can be regulated extremely precisely as a result.

The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
DVGW odobritev	DIN EN 13828:2003-12, DVGW W 570
Kolo	Plastic
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G 1
Ohišje	Nickel-plated brass (outside), brass with a bare metal surface (inside)
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	NBR
DN	25
Max. obratovalni tlak [bar]	40
L [mm]	68.8
B [mm]	80.0
A [mm]	83.0
Max. delovna temperatura [°C]	100