

Datum: 13.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## [krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 1 1/4](#)

Kategorija: [Brass ball valves, double-acting actuator](#)  
Šifra: **103527RIE**

(slika je simbolična)

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive double-acting, Operating temperature max. 70°C, Rp 1 1/4, DN 32, PN max. 40 bar  
2-way cock, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1 1/4
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
D [mm]	30.0
DN	32
PN [bar]	40
a/f [mm]	50
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	110.0
A [mm]	116.0
B [mm]	150.0