



(slika je simbolična)

[krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 3/4](#)

Kategorija: [Brass ball valve, double-acting actuator](#)
Šifra: **103566RIE**

Kratek opis

Brass ball valve, Pneumat. actuation drive, double-acting,
Operating temperature -20 °C to 150 °C, Rp 3/4, DN 20, PN
max. 16 bar
Ball valves with pneumatic actuator.
Pneumatic, double-piston, part-turn actuator, double-rocker
principle.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Min. temperaturno območje [°C] | -20 |
| Adapter ventila | Supplied as standard |
| Material krogelnega ventila | Nickel-plated brass, with ISO flange plate |
| Navoj | Rp 3/4 |
| Pogonski material | Anodised aluminium |
| Premaz za krogelni ventil | PTFE / FKM |
| Premaz za pogon | NBR |
| Različica | double-acting |
| Max. vodeni tlak [bar] | 5.6 |
| Max. obratovalni tlak [bar] | 16 |
| DN | 20 |
| A [mm] | 70.0 |
| L [mm] | 77.0 |
| Max. temperaturno območje [°C] | 80 |
| Kot vrtenja [°] | 90 |
| B [mm] | 94.0 |
| Max. delovna temperatura [°C] | 150 |