

Datum: 21.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

krogelni ventil medenina, pnevmatski vklop vzmetni preklop, Rp 3

Kategorija: [Brass ball valve, single-acting actuator](#)
Šifra: **103539RIE**

(slika je simbolična)

Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring switching, Operating temp. max. 70 °C, Rp 3, DN 80, PN max. 16 bar
2-way cock, full bore.
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 3
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
PN [bar]	16
D [mm]	68.0
Max. delovna temperatura [°C]	70
DN	80
Kot vrtenja [°]	90
a/f [mm]	98
L [mm]	182.0
A [mm]	209.0
B [mm]	242.0