



(slika je simbolična)

krogelni ventil nerjavno jeklo, električni vklop, Rp 1

Kategorija: [Stainless steel ball valve, actuator 230 VAC 50 Hz](#)Šifra: **103708RIE**

Kratek opis

2-way stainless steel ball valve, Electr. actuation drive, 230 V AC, 50 Hz, Medium temp. -10 °C to 200 °C, Rp 1, PN max. 63 bar
Voltage range 230 VAC, 50 Hz or 24 VDC.
Reversible electric rotary actuator.

Tehnične Specifikacije

| | |
|------------------------------|---------------------------------|
| Min. sobna temperatura [°C] | -30 |
| Min. temperatura medija [°C] | -10 |
| Dolžina | DIN 3203 - M3 |
| Indikator položaja | Manually operated |
| IP zaščita | IP 68 |
| Krogelno tesnilo | PTFE, glass fibre-reinforced |
| Material | Stainless steel 1.4401 / 1.4408 |
| Montažna prirobnica | ISO 5211 |
| Navoj | Rp 1 |
| Ohišje | Aluminium powder-coated |
| Tesnilo gredi izbirnika | PTFE, glass fibre-reinforced |
| Čas aktivacije [sec.] | 15 |
| D [mm] | 20.5 |
| DN | 25 |
| Delovni cikel [%] | 30 |
| Relativna vlažnost | 30 % to 95 % |
| a/f [mm] | 41 |
| Max. obratovalni tlak [bar] | 63 |
| Max. sobna temperatura [°C] | 70 |
| L [mm] | 90.0 |
| A [mm] | 153.0 |
| B [mm] | 158.0 |
| Max. temperatura medija [°C] | 200 |
| Napetost | 230 VAC, 50 Hz |