

Datum: 12.06.2026



(slika je simbolična)

## [krogelni ventil nerjavno jeklo, električni vklop, Rp 2](#)

Kategorija: [Stainless steel ball valve, actuator 230 VAC 50 Hz](#)Šifra: **103711RIE**

### Kratek opis

2-way stainless steel ball valve, Electr. actuation drive, 230 V AC, 50 Hz, Medium temp. -10 °C to 200 °C, Rp 2, PN max. 63 bar  
Voltage range 230 VAC, 50 Hz or 24 VDC.  
Reversible electric rotary actuator.

### Tehnične Specifikacije

|                              |                                 |
|------------------------------|---------------------------------|
| Min. sobna temperatura [°C]  | -30                             |
| Min. temperatura medija [°C] | -10                             |
| Dolžina                      | DIN 3203 - M3                   |
| Indikator položaja           | Manually operated               |
| IP zaščita                   | IP 68                           |
| Krogelno tesnilo             | PTFE, glass fibre-reinforced    |
| Material                     | Stainless steel 1.4401 / 1.4408 |
| Montažna prirobnica          | ISO 5211                        |
| Navoj                        | Rp 2                            |
| Ohišje                       | Aluminium powder-coated         |
| Tesnilo gredi izbirnika      | PTFE, glass fibre-reinforced    |
| Čas aktivacije [sec.]        | 22                              |
| Delovni cikel [%]            | 30                              |
| Relativna vlažnost           | 30 % to 95 %                    |
| D [mm]                       | 36.5                            |
| DN                           | 50                              |
| Max. obratovalni tlak [bar]  | 63                              |
| Max. sobna temperatura [°C]  | 70                              |
| a/f [mm]                     | 73                              |
| L [mm]                       | 140.0                           |
| A [mm]                       | 153.0                           |
| Max. temperatura medija [°C] | 200                             |
| B [mm]                       | 201.0                           |
| Napetost                     | 230 VAC, 50 Hz                  |