



## krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 2 1/2

Kategorija: [Stainless steel ball valve, single-acting actuator](#)  
Šifra: **103612RIE**

(slika je simbolična)

### Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, single-acting, Operating temp. -20°C to 70°C, Rp 2 1/2, PN max 63 bar

2-way cock, 3-piece, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate Rp 2 1/2
Navoj	Anodised aluminium
Pogonski material	PTFE
Premaz za krogelni ventil	NBR
Premaz za pogon	single-acting - spring to close
Različica	
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
D [mm]	60.0
Max. obratovalni tlak [bar]	63
DN	65
Max. delovna temperatura [°C]	70
a/f [mm]	85
Kot vrtenja [°]	90
L [mm]	185.0
A [mm]	221.0
B [mm]	268.0