



(slika je simbolična)

## [krogelni ventil nerjavno jeklo, Pneumat. vklop, L-izpust](#)

Kategorija: [Stainless steel ball valve, double-acting, L-bore](#)  
Šifra: **103617RIE**

### Kratek opis

3-way stainless steel ball valve, Pneumat. actuation drive, L-hole, Operating temp. -20°C to 70°C, Rp 1 1/4, DN 32, PN max 63 bar

3-way cock, reduced bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate
Navoj	Rp 1 1/4
Pogonski material	Anodised aluminium
Položaj	L 2
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
DN	32
D [mm]	36.5
a/f [mm]	50
Max. obratovalni tlak [bar]	63
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	90.0
A [mm]	133.0
B [mm]	153.5