

Datum: 21.04.2026



## krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 1 1/2

Kategorija: [Stainless steel ball valve, single-acting actuator](#)  
Šifra: **103610RIE**

(slika je simbolična)

### Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, single-acting, Operating temp. -20°C to 70°C, Rp 1 1/2, PN max 63 bar

2-way cock, 3-piece, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate Rp 1 1/2
Navoj	Rp 1 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE
Premaz za pogon	NBR
Različica	single-acting - spring to close
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
D [mm]	40.0
DN	40
a/f [mm]	58
Max. obratovalni tlak [bar]	63
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	120.0
A [mm]	180.0
B [mm]	198.0