

Datum: 21.04.2026



(slika je simbolična)

## krogelni ventil nerjavno jeklo, Pneumat. vklop, Rp 1

Kategorija: [Stainless steel ball valve, single-acting actuator](#)  
Šifra: **103608RIE**

### Kratek opis

2-way stainless steel ball valve, Pneumat. actuation drive, single-acting, Operating temp. -20 °C to 70 °C, Rp 1, PN max. 63 bar  
2-way cock, 3-piece, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.  
Standardised interfaces:  
Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.  
Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.  
Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Min. delovna temperatura [°C]     | -20                                |
| Adapter ventila                   | Acc. to NAMUR<br>Stainless steel   |
| Material krogelnega ventila       | 1.4401, with ISO<br>flange plate   |
| Navoj                             | Rp 1                               |
| Pogonski material                 | Anodised aluminium                 |
| Premaz za krogelni ventil         | PTFE                               |
| Premaz za pogon                   | NBR                                |
| Različica                         | single-acting - spring<br>to close |
| Priporočeni vodeni tlak [bar]     | 5.5                                |
| Max. vodeni tlak aktuatorja [bar] | 10                                 |
| DN                                | 25                                 |
| D [mm]                            | 33.0                               |
| a/f [mm]                          | 41                                 |
| Max. obratovalni tlak [bar]       | 63                                 |
| Max. delovna temperatura [°C]     | 70                                 |
| Kot vrtenja [°]                   | 90                                 |
| L [mm]                            | 90.0                               |
| A [mm]                            | 137.0                              |
| B [mm]                            | 170.0                              |