

Datum: 01.07.2026



krogelni ventil nerjavno jeklo, Pneumat. vklop, T-izpust T2

Kategorija: [Stainless steel ball valve, double-acting, T-bore](#)Šifra: **103637RIE**

(slika je simbolična)

Kratek opis

3-way stainless steel ball valve, Pneumat. actuation drive, T-hole T2, Operating temp. -20°C to 70°C, Rp 2, DN 50, PN max. 63 bar

3-way cock, reduced bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Tehnične Specifikacije

| | |
|-----------------------------------|----------------------------------|
| Min. delovna temperatura [°C] | -20 |
| Adapter ventila | Acc. to NAMUR Stainless steel |
| Material krogelnega ventila | 1.4401, with ISO flange plate |
| Navoj | Rp 2 |
| Pogonski material | Anodised aluminium |
| Položaj | T 2 |
| Premaz za krogelni ventil | PTFE / FKM |
| Premaz za pogon | NBR |
| Različica | double-acting |
| Priporočeni vodeni tlak [bar] | 5.5 |
| Max. vodeni tlak aktuatorja [bar] | 10 |
| D [mm] | 47.5 |
| DN | 50 |
| Max. obratovalni tlak [bar] | 63 |
| Max. delovna temperatura [°C] | 70 |
| a/f [mm] | 71 |
| Kot vrtenja [°] | 90 |
| L [mm] | 115.0 |
| A [mm] | 161.0 |
| B [mm] | 196.5 |