

Datum: 13.04.2026



## [krogelni ventil nerjavno jeklo, Pneumat. vklop, L-izpust](#)

Kategorija: [Stainless steel ball valve, double-acting, L-bore](#)Šifra: **103615RIE**

(slika je simbolična)

### Kratek opis

3-way stainless steel ball valve, Pneumat. actuation drive, L-hole, Operating temp. -20°C to 70°C, Rp 3/4, DN 20, PN max. 63 bar

3-way cock, reduced bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate Rp 3/4
Navoj	Anodised aluminium
Pogonski material	L 2
Položaj	PTFE / FKM
Premaz za krogelni ventil	NBR
Premaz za pogon	double-acting
Različica	5.5
Priporočeni vodeni tlak [bar]	10
Max. vodeni tlak aktuatorja [bar]	20
DN	23.0
D [mm]	32
a/f [mm]	63
Max. obratovalni tlak [bar]	70
Max. delovna temperatura [°C]	80.0
L [mm]	90
Kot vrtenja [°]	116.0
A [mm]	136.0
B [mm]	