



## krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 1/2

Kategorija: [Stainless steel ball valve, double-acting actuator](#)  
Šifra: **158754RIE**

(slika je simbolična)

### Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 1/2, PN max. 100 bar  
Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

|                                           |                                              |
|-------------------------------------------|----------------------------------------------|
| Min. delovna temperatura aktuatorja [°C]  | -20                                          |
| Min. delovni tlak krogelnega ventila [°C] | -20                                          |
| Adapter ventila                           | Integrated to NAMUR                          |
| Material                                  | Stainless steel                              |
| krogelnega ventila                        | 1.4401/1.4301/1.4310/1.4408, with ISO flange |
| Navoj                                     | Rp 1/2                                       |
| Pogonski material                         | Anodised aluminium                           |
| Premaz za krogelni ventil                 | PTFE / FKM                                   |
| Premaz za pogon                           | NBR                                          |
| Različica                                 | double-acting                                |
| Priporočeni vodeni tlak [bar]             | 5.6                                          |
| Max. vodeni tlak aktuatorja [bar]         | 8.4                                          |
| DN                                        | 15                                           |
| L [mm]                                    | 65.0                                         |
| Max. delovna temperatura aktuatorja [°C]  | 80                                           |
| Kot vrtenja [°]                           | 90                                           |
| PN [bar]                                  | 100                                          |
| B [mm]                                    | 147.0                                        |
| Max. delovni tlak krogelnega ventila [°C] | 150                                          |
| A [mm]                                    | 159.0                                        |