

krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 1



Kategorija: [Stainless steel ball valve, double-acting actuator](#)
Šifra: **158756RIE**

(slika je simbolična)

Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 1, PN max. 100 bar
Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Integrated to NAMUR
Material krogelnega ventila	Stainless steel
Navoj	1.4401/1.4301/1.4310/1.4408, with ISO flange
Pogonski material	Rp 1
Premaz za krogelni ventil	Anodised aluminium
Premaz za pogon	PTFE / FKM
Različica	NBR
Priporočeni vodeni tlak [bar]	double-acting
Max. vodeni tlak aktuatorja [bar]	5.6
DN	8.4
Max. delovna temperatura aktuatorja [°C]	25
L [mm]	80
Kot vrtenja [°]	85.0
PN [bar]	90
Max. delovni tlak krogelnega ventila [°C]	100
B [mm]	150
A [mm]	160.5
	174.2