



krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 2

Kategorija: [Stainless steel ball valve, double-acting actuator](#)
Šifra: **103587RIE**

(slika je simbolična)

Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 2, PN max. 40 bar
Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Min. temperaturno območje [°C] | -20 |
| Adapter ventila | Supplied as standard |
| Material krogelnega ventila | Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange |
| Navoj | Rp 2 |
| Pogonski material | Anodised aluminium |
| Premaz za krogelni ventil | PTFE / FKM |
| Premaz za pogon | NBR |
| Različica | double-acting |
| Max. vodeni tlak [bar] | 5.6 |
| PN [bar] | 40 |
| DN | 50 |
| Max. temperaturno območje [°C] | 80 |
| Kot vrtenja [°] | 90 |
| L [mm] | 125.0 |
| Max. delovna temperatura [°C] | 150 |
| A [mm] | 169.0 |
| B [mm] | 196.0 |