

Datum: 12.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## [krogelni ventil nerjavno jeklo, za DIN 3202-M3, G 1](#)

Kategorija: [Ball valves 3-piece, length acc. to DIN 3202-M3](#)  
Šifra: **135914RIE**

### Kratek opis

Stainless steel ball valve, 3-piece, length acc. to DIN 3202-M3, G 1, DN 25, Operating temp. -20 °C to 180 °C, PN max. 63 bar

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock ISO 5211	ca. 7.7 mm
Krogelno tesnilo	PTFE (15 % glass fibre reinforced)
Krogla	Stainless steel 1.4401
Navoj	G 1
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1, flange plate ISO 5211
Stebelno tesnilo	PTFE
DN	25
PN [bar]	63
B [mm]	88.5
L [mm]	90.0
A [mm]	150.0
Max. delovna temperatura [°C]	180