

Datum: 12.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[krogelni ventil nerjavno jeklo, za DIN 3202-M3, G 3/4](#)

Kategorija: [Ball valves 3-piece, length acc. to DIN 3202-M3](#)
Šifra: **135913RIE**

Kratek opis

Stainless steel ball valve, 3-piece, length acc. to DIN 3202-M3, G 3/4, DN 20, Operating temp. -20 °C to 180 °C, PN max. 63 bar

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Bore diameter padlock ISO 5211 | ca. 7.7 mm F 03 / F 04 |
| Krogelno tesnilo | PTFE (15 % glass fibre reinforced) |
| Krogla | Stainless steel 1.4401 |
| Navoj | G 3/4 |
| Ohišje | Stainless steel 1.4408 |
| Ročica | Stainless steel 1.4301, with plastic coating |
| Standardni navoj | G thread acc. to DIN EN ISO 228-1, flange plate ISO 5211 |
| Stebelno tesnilo | PTFE |
| C Ø [mm] | 20.0 |
| DN | 20 |
| PN [bar] | 63 |
| L [mm] | 80.0 |
| B [mm] | 81.5 |
| A [mm] | 125.0 |
| Max. delovna temperatura [°C] | 180 |