



(slika je simbolična)

[krogelni ventil nerjavno jeklo, za DIN 3202-M3, G 3](#)

Kategorija: [Ball valves 3-piece, length acc. to DIN 3202-M3](#)
Šifra: **135919RIE**

Kratek opis

Stainless steel ball valve, 3-piece, length acc. to DIN 3202-M3, G 3, DN 80, Operating temp. -20 °C to 180 °C, PN max. 40 bar

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Bore diameter padlock ISO 5211 | ca. 7.7 mm |
| Krogelno tesnilo | PTFE (15 % glass fibre reinforced) |
| Krogla | Stainless steel 1.4401 |
| Navoj | G 3 |
| Ohišje | Stainless steel 1.4408 |
| Ročica | Stainless steel 1.4301, with plastic coating |
| Standardni navoj | G thread acc. to DIN EN ISO 228-1, flange plate ISO 5211 |
| Stebelno tesnilo | PTFE |
| PN [bar] | 40 |
| C Ø [mm] | 76.0 |
| DN | 80 |
| B [mm] | 136.0 |
| Max. delovna temperatura [°C] | 180 |
| L [mm] | 205.0 |
| A [mm] | 350.0 |