

Datum: 26.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[krogelni ventil robustnejša oblika, Z ročico, ročni, ET/ET, R 1](#)

Kategorija: [Ball valve with hand lever, ET/ET](#)
Šifra: **103283RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, ET/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, R 1, PN max. 100 bar
Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	R 1
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	R thread acc. to DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
E [mm]	19.0
F [mm]	19.0
DN	25
a/f [mm]	40
B [mm]	80.0
PN [bar]	100
L [mm]	107.0
A [mm]	120.0
Max. delovna temperatura [°C]	130