

Datum: 12.05.2026



(slika je simbolična)

## [krogelni ventil robustnejša oblika, Z ročico, ročni, ET/ET, R 3/8](#)

Kategorija: [Ball valve with hand lever, ET/ET](#)  
Šifra: **103280RIE**

### Kratek opis

Ball valve heavy duty design, Manual lever, ET/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, R 3/8, PN max. 100 bar  
Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

### Tehnične Specifikacije

|                               |   |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -20                                     |
| Krogelno tesnilo              | PTFE                                    |
| Krogla                        | Chrome-plated brass                     |
| Material navojev              | Brass with a bare metal surface         |
| Navoj                         | R 3/8                                   |
| Ohišje                        | Nickel-plated brass                     |
| Ročica                        | Aluminium, painted black                |
| Standardni navoj              | R thread acc. to DIN EN 10226 (ISO 7-1) |
| Stebelno tesnilo              | PTFE                                    |
| DN                            | 10                                      |
| E [mm]                        | 11.2                                    |
| F [mm]                        | 11.2                                    |
| a/f [mm]                      | 22                                      |
| B [mm]                        | 61.0                                    |
| L [mm]                        | 66.0                                    |
| A [mm]                        | 100.0                                   |
| PN [bar]                      | 100                                     |
| Max. delovna temperatura [°C] | 130                                     |