

Datum: 20.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## [krogelni ventil robustnejša oblika, Z ročico, ročni, IT/IT, G 2](#)

Kategorija: [Ball valve with hand lever, IT/IT](#)  
Šifra: **103268RIE**

### Kratek opis

Ball valve heavy duty design, Manual lever, IT/IT, nickel-plated brass, Operating temp. -20 °C to 130 °C, G 2, PN max. 63 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G 2
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE
E [mm]	20.5
F [mm]	20.5
DN	50
PN [bar]	63
a/f [mm]	69
B [mm]	115.5
L [mm]	121.0
Max. delovna temperatura [°C]	130
A [mm]	175.0